# SMART SOLUTIONS FOR THE LABELING INDUSTRY

## UNWINDER & REWINDER FOR SWIFTCOLOR SCL-4000D LABEL PRINTER





LABEL REWINDER (ASDIIII-SD) - SwiftColor SCL-4000D Printer - LABEL UNWINDER (ASSIIII-SD) (Not included)

The rewinder and unwinder for Swiftcolor SCL-4000D printers are used to manage rolls of media up to 5" (127mm) wide having an outside diameter up to 10" (250mm). The users can select among the adjustable core holder from 1.57" up to 4.64" (40-118mm).

To guarantee an aligned media path in the system, it is available the junction plate to connect the rewinder and unwinder together. It offers also a customized sliding support where lean and fix the printer.

#### Electronic and mechanical features:

An external power supply 100/240VAC - 2.5A == at 24V allows an electronic circuit to provide, through the tension arm, the automatic adjustment of the rotation direction and speed.

The unwinder / rewinder have two types of speed adjustments, through the two buttons it is possible to set the maximum speed required while the tension arm will auto adjust the speed from zero to the set value. The control panel allows to set the label rewinding face-in or face-out option.



#### LABEL UNWINDER

The position of the tension arm is calibrated as follows:

- When the printer forwards the media for printing, the tension arm goes up and the device unwinds the media.
- When the tension arm is in the middle position, the device is idle.
- When the printer pulls back the media, the tension arm goes down and the device rewinds it.



### LABEL REWINDER

The position of the tension arm is calibrated as follows:

- When the printer forwards the media for printing, the tension arm goes down and the device rewinds the media.
- When the tension arm is in the middle position, the device is idle.
- When the printer pulls back the media, the tension arm goes up and the device unwinds it.



